

VENTILCONVETTORE Versione **VE**
FAN CONVECTORS VE Versions

Riscaldamento ad acqua / Water heating			
Potenzialità termica con temperatura acqua entrante 70° C uscita 58° C Alla portata aria massima Aria ambiente 20° C 50% UR <i>Thermal capacity with an inbound water temperature equal to 70° C and an outbound water temperature of 58° C</i> <i>At maximum air flow</i> <i>Room temperature 20° C and 50% UR</i>	vel. Max. <i>Max. speed</i>	kCal/h	5300
	vel. Med. <i>Med. speed</i>	kCal/h	3600
	vel. Min. <i>Min. speed</i>	kCal/h	1300
	vel. Max. <i>Max. speed</i>	kW	6.16
	vel. Med. <i>Med. speed</i>	kW	4.17
	vel. Min. <i>Min. speed</i>	kW	1.51
	Portata acqua <i>Water flow rate</i>	l/h	500
Potenzialità termica Con temperatura acqua entrante 50° C uscita 47° C Portata aria massima Aria ambiente 20° C 50% UR <i>Thermal capacity with an inbound water temperature equal to 50° C and an outbound water temperature of 47° C</i> <i>At maximum air flow</i> <i>Room temperature 20° C and 50% UR</i>	vel. Max. <i>Max. speed</i>	Frig/h	3100
	vel. Med. <i>Med. speed</i>	Frig/h	2200
	vel. Min. <i>Min. speed</i>	Frig/h	800
	vel. Max. <i>Max. speed</i>	kW	3.60
	vel. Med. <i>Med. speed</i>	kW	2.56
	vel. Min. <i>Min. speed</i>	kW	0.93
	Portata acqua <i>Water flow rate</i>	l/h	500
Condizionamento ad acqua / Water air conditioning			
Potenzialità frigorifera totale Con temperatura acqua entrante 7° C uscita 12° C Alla portata aria massima aria ambiente 27° C B.S. 19° C B.U. <i>Total cooling capacity with an inbound water temperature equal to 7° C and an outbound water temperature of 12° C</i> <i>At maximum air flow</i> <i>Room temperature 27° C B.S. and 19° C B.U.</i>	vel. Max. <i>Max. speed</i>	Frig/h	2050
	vel. Med. <i>Med. speed</i>	Frig/h	1600
	vel. Min. <i>Min. speed</i>	Frig/h	750
	vel. Max. <i>Max. speed</i>	kW	2.38
	vel. Med. <i>Med. speed</i>	kW	1.86
	vel. Min. <i>Min. speed</i>	kW	0.87
	Potenzialità frigorifera sensibile <i>Cooling capacity sensible</i>	vel. Max. <i>Max. speed</i>	Frig/h
vel. Med. <i>Med. speed</i>		Frig/h	1300
vel. Min. <i>Min. speed</i>		Frig/h	620
vel. Max. <i>Max. speed</i>		kW	1.93
vel. Med. <i>Med. speed</i>		kW	1.51
vel. Min. <i>Min. speed</i>		kW	0.72
Portata acqua <i>Water flow rate</i>		l/h	500

Dati riferiti ad un singolo elettroventilatore.
Reported data to a single electric fan.

Caratteristiche - Characteristics

Portata aria - Air flow	vel. Max. <i>Max. speed</i>	m³/h	550
	vel. Med. <i>Med. speed</i>	l/s	153
	vel. Min. <i>Min. speed</i>	m³/h	320
	vel. Min. <i>Min. speed</i>	l/s	90
Potenza massima assorbita da un ventilatore <i>Maximum power absorbed by the fan</i>	W	105	
Corrente massima assorbita da un ventilatore <i>Maximum capacity absorbed by the fan</i>	A	0.5	
Tensione di alimentazione <i>Supply voltage</i>	Volt/Fasi/Hertz	230/1/50	
Livello di pressione sonora a 3 mt campo semisferico con canali e bocchette montate <i>Sound pressure level taken 3 m from the unit in a hemispherical field with mounted ducts and nozzles</i>	vel. Max. <i>Max. speed</i>	dB(A)	39
	vel. Med. <i>Med. speed</i>	dB(A)	31
	vel. Min. <i>Min. speed</i>	dB(A)	22
Numero di ranghi batteria <i>Number of battery ranks</i>	Acqua - Water n.	4	
Diametro attacchi batteria <i>Battery socket diameter</i>	Ad acqua - Water Ø	3/4	
Diametro scarico condensa <i>Condensation exhaust diameter</i>	mm	22	
Peso di ogni singola bocca <i>Weight of each nozzle</i>	Kg	13	